



NOTE 1. FIT LOCK PLATE, ITEM 18, BEHIND REAR CLIPS, 2 POSNS, LOCK IN POSN. USING ITEMS 33 & 37 AS SHOWN BELOW.



2. USE HOT MELT ADHESIVE, ITEM 30, TO RETAIN SPEAKERS.  
3. ENSURE DISC DRIVE DATA CABLE RED STRIPE IS CLOSEST TO THE FRONT OF THE MACHINE.



SPEAKER CABLE ROUTING DETAIL N.T.S.

SCALE	HALF SIZE	ALL DIMENSIONS IN mm UNLESS OTHERWISE STATED
MATERIAL	SEE 0080,000/P	
FINISH		
WHOLE No. TOL.	DECIMAL No. TOL.	ANGLE TOL.

Copyright of this drawing is reserved by ACORN COMPUTERS LTD. It is issued on condition that it is not copied, reproduced or disclosed to a third party, either wholly or in part, without the consent in writing of ACORN COMPUTERS LTD.



© COPYRIGHT 1988  
ACORN COMPUTERS LTD.  
FULBURN ROAD  
CHERRY HINTON  
CAMBRIDGE CB1 4JN

TITLE  
A3000 FINAL ASSEMBLY

ACORN COMPUTERS Ltd

A0 DRG. No. 0080,000 /A

2	12	ECO 2269	PMK	
1	11	AMR 2339	BS	
B	28	ITEM 33 WAS 29	BS	
A	20	INITIAL ISSUE	BS	PMK
ISS DATE	DESC. OF CHANGE	DRN.	CHKD.	